



## Specification.

### 1.0mm Sheet metal

*Outer enclosure  
Back cover  
Cover plates  
Left/right changeable door*

### 1.5mm Sheet metal

*Mount plate*

### Lock

*Plated Triangle metal lock*

### Surface finish

*Powder coated to 100µm  
RAL7032 as standard*

### Protection degree

*IP - 54*

### Construction includes

*Removable hinges  
Gasket at door  
Earth studs  
Gland plates*

Model	W <sub>in mm</sub>	H <sub>in mm</sub>	D <sub>in mm</sub>
E - 20 - 20 - 15	200	200	150
E - 25 - 30 - 15	250	300	150
E - 25 - 30 - 20	250	300	200
E - 30 - 30 - 15	300	300	150
E - 30 - 30 - 20	300	300	200
E - 30 - 40 - 15	300	400	150
E - 30 - 40 - 20	300	400	200
E - 40 - 40 - 15	400	400	150
E - 40 - 40 - 20	400	400	200
E - 40 - 50 - 15	400	500	150
E - 40 - 50 - 20	400	500	200
E - 40 - 60 - 15	400	600	150
E - 40 - 60 - 20	400	600	200
E - 50 - 60 - 20	500	600	200
E - 50 - 60 - 25	500	600	250
E - 60 - 60 - 20	600	600	200
E - 60 - 60 - 25	600	600	250
E - 50 - 70 - 20	500	700	200
E - 50 - 70 - 25	500	700	250
E - 60 - 70 - 20	600	700	200
E - 60 - 70 - 25	600	700	250
E - 60 - 80 - 20	600	800	200
E - 60 - 80 - 25	600	800	250
E - 60 - 100 - 20	600	1000	200
E - 60 - 100 - 25	600	1000	250
E - 80 - 100 - 20	800	1000	200
E - 80 - 100 - 25	800	1000	250
E - 60 - 120 - 20	600	1200	200
E - 60 - 120 - 25	600	1200	250
E - 80 - 120 - 25	800	1200	250